





-
- -
 -
 -
 -
 -
 -
 -
 -

2.1		

■



	SCARA
	...




		1
1.1		2
1.2		2
1.3		3



SCARA

IO

1.1



1.2



1-1

	S/N P/N

1.3

1	
HRC	

2	
2	

3	
A	220V
S	220V
T	380V

4	
J	J3
X	X3
Y	Y7

6	
-	
F	
M	

- 1.
2.



2.1


.....	4
.....	5



2-1	
-----	--

kg	3	6		10	20
----	---	---	--	----	----

5




		6
3.1		7
3.2		7
3.3		7



3.1

- 1.
- 2.



3.2

1. -20°C +65°C
2. 0% 90%
- 3.

3.3

- 1.
- 2.
- 3.
- 4.

1. 0°C 55°C
- 2.
- 3.
- 4.
- 5.
- 6.



..... 8



1.

NC

2.

3.



		10
5.1		12
5.2		12
5.3		13
5.3.1		13
5.3.2	EtherCAT	13
5.3.3	EtherNet	14
5.3.4	RS485/RS232	14
5.3.5		15
5.3.6		15
5.3.7		16
5.3.8		17
5.3.9	IO	18




...

			
			
	DC	AC	
	U V W 10		

/

IO



5-1

5.1



5-2

5-1

5.2

1.

MOTOR
ENC
2.

TP
3.

AC220V

1 "L" 2 "N" 3 "PE"

16A
4.


IO
IO
PNP NPN
NPN

5.

5.3

5.3.1

200-240V 50/60HZ 1.5mm²



5-3


5-2

1	L	AC220V
2	N	
3	PE	

5.3.2 EtherCAT

EtherCAT RJ45 8 100M, IO

8



5-4 EtherCAT

5-3 EtherCAT

1	TX+	+	5		—
2	TX-	-	6	RX-	-
3	RX+	+	7		—
4		—	8	GND	

5.3.3 EtherNet

EtherNet/IP

TCP/UDP

IEEE802.3U

EtherNet/IP

I/O

/

/PLC/

5-4 EtherNet

1	TXP	+	5		—
2	TXN	-	6	RXN	-
3	RXP	+	7		—
4		—	8	GND	

5.3.4 RS485/RS232

RS485/232

4800-115200

RS485

500

32


RS232

15

RS232

1

5



5-5 RS485/232

5.3.5

SCARA

“ ”

5-6 TP

1	EtherNet TX+	+	9	A	A
2	EtherNet TX-	-	10	24V	24V
3	EtherNet RX+	+	11	24V	24V
4	EtherNet RX-	-	12	0V	0V
5	COM		13	0V	0V
6	NO		14	PE	
7	NC		15	ST2	2
8	B	B	16	ST1	1

5.

5-7 ENC

			13	J3D+	J3 +
			17	J1-J2屏蔽线	J1-J2
5	J3-J4屏蔽线	J3-J4	18	J2GND	J2 -
6	J4GND	J3 -	19	J2BAT+ J	J2 +
7	J4BAT+ J	J4 +	20	J2D-	J2 +
8	J4D-	J4 +	21		4

5.3.8

24V

SS

DC24V

+20%~-15%
1.5KVrms

4.86K Ω

7mA/DC24V,

5KHz,

0.1ms


NPN

0.25A/


5KHz

0.1ms


1.5KVrms




5-9 CN1


[illegible]

5-10 CN1





5-12 CN1



5-13 CN1



5-14



		19
6.1		20
6.2		20



J ± -

r

1

C

² -

M ± -

F

R





		21
7.1		22
7.2		22



7.1

 重 要	Err.097				
	3.0V	Err.015	15		3.0V
	Err.012			2.7 V	
	5				
					7-1

7-1


	SV-ENC-BAT
	3.6V
	2.7Ah
(D x H)	17 mm x 55 mm
	25g

7.2


1



2



3



4 “L”

5 4 “L”

6

7

hCF

